

1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 SE 1/4 Section Number 9 Township Number T 24 S Range Number R 1 E/W

County: SEDGWICK Distance and direction from nearest town or city street address of well if located within city? 8810 S. LULU WICHITA KANSAS 67233

2 WATER WELL OWNER: CLARENCE SCHULTZ RR#, St. Address, Box #: 8810 S. LULU City, State, ZIP Code: WICHITA KANSAS 67233 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE section]

4 DEPTH OF COMPLETED WELL: 26 ft. ELEVATION: 11 ft. below land surface measured on mo/day/yr 5-25-85

Depth(s) Groundwater Encountered: 1. 11 ft. 2. 30 ft. 3. 30 ft.

WELL'S STATIC WATER LEVEL: 11 ft. below land surface measured on mo/day/yr 5-25-85

Pump test data: Well water was 11 ft. after 2 hours pumping 30 gpm

Est. Yield: 50 gpm: Well water was 11 ft. after 2 hours pumping 30 gpm

Bore Hole Diameter: 7 in. to 26 ft., and 30 in. to 30 ft.

WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 5 in. to 12 ft. Dia. 12 in. to 2.37 lbs./ft. Wall thickness or gauge No. 250

Casing height above land surface: 12 in., weight 2.37 lbs./ft.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 12 ft. to 26 ft. From 12 ft. to 26 ft. From 12 ft. to 26 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 26 ft. From 10 ft. to 26 ft. From 10 ft. to 26 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL

Grout Intervals: From 3 ft. to 10 ft. From 3 ft. to 10 ft. From 3 ft. to 10 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? SOUTH EAST How many feet? 50

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-25-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 5-29-85 under the business name of RALPH THE TOWER WELL DIGGER DRILLING RALPH S. MITCHELL

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.