


1 LOCATION OF WATER WELL: Fraction SE 1/4 SW 1/4 SE 1/4 Section Number 9 Township Number T 29 S Range Number R 10 E
 County Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: JOEL BASINGER
 RR#, St. Address, Box #: 1309 E 86th St
 City, State, ZIP Code: HAYSVILLE KS 67050
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 9-3-90
 Depth(s) Groundwater Encountered: 16 ft. 2. 16 ft. 3. 16 ft.
 WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 16 ft. after 20 hours pumping 20 gpm
 Est. Yield 75 gpm Well water was 16 ft. after 20 hours pumping 20 gpm
 Bore Hole Diameter: 11 in. to 36 ft., and 11 in. to 36 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped
☐ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded
☐ 3 Fiberglass ☐ Threaded
 Blank casing diameter: 5 in. to 26 ft. Dia. 26 in. to 26 ft. Dia. 26 in. to 26 ft.
 Casing height above land surface: 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160A128
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 26 ft. to 36 ft. From 26 ft. to 36 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 36 ft. From 18 ft. to 36 ft.

6 GROUT MATERIAL: ☒ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 18 ft. From 3 ft. to 18 ft. From 3 ft. to 18 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? South How many feet? 140

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	12	clay			
12	19	fine sand			
19	20	clay			
20	36	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-3-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 378-90 This Water Well Record was completed on (mo/day/yr) 9-13-90 under the business name of Livingston Dull by (signature) [Signature]