

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NW ¼ SE ¼ NE ¼	9	T 29 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?
8210 Lulu Wichita, KS 67233

2) WATER WELL OWNER: Jim HENDRICKS RR#, St. Address, Box #: 3939 N. SOMERSET City, State, ZIP Code: WICHITA MS 67204		Board of Agriculture, Division of Water Resources Application Number:
--	--	--

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:	
---	--	---	--

Depth(s) Groundwater Encountered 11 ft.

WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 12-3-92

Pump test data: Well water was 11 ft. after 2 hours pumping 30 gpm

Est. Yield 45 gpm: Well water was 11 ft. after 2 hours pumping 30 gpm

Bore Hole Diameter 11 in. to 29 ft., and . in. to . ft.

WELL WATER TO BE USED AS:
☒ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Injection well
☐ Irrigation ☐ Industrial ☐ Lawn and garden only ☐ Monitoring well ☐ Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ☒ No

5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped	
-------------------------------	--	--	--

☒ Steel ☐ RMP (SR)
☒ PVC ☐ ABS
Blank casing diameter 5 in. to 20 ft., Dia . in. to . ft., Dia . in. to . ft.
Casing height above land surface 20 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250

TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ Steel ☐ Stainless steel ☐ Fiberglass ☐ RMP (SR)
☐ Brass ☐ Galvanized steel ☐ Concrete tile ☐ ABS

SCREEN OR PERFORATION OPENINGS ARE:
☐ Continuous slot ☐ Mill slot ☐ Wire wrapped ☒ Saw cut ☐ None (open hole)
☐ Louvered shutter ☐ Key punched ☐ Torch cut ☐ Drilled holes ☐ Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 29 ft., From . ft. to . ft., From . ft. to . ft., From . ft. to . ft.

GRAVEL PACK INTERVALS: From 20 ft. to 29 ft., From . ft. to . ft., From . ft. to . ft., From . ft. to . ft.

6) GROUT MATERIAL: ☒ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other 0-3' SURFACE SOIL

Grout Intervals: From 3 ft. to 11 ft., From 11 ft. to 20 ft., From . ft. to . ft., From . ft. to . ft.

What is the nearest source of possible contamination:
☒ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Abandoned water well
☐ Sewer lines ☐ Cess pool ☐ Sewage lagoon ☐ Fuel storage ☐ Oil well/Gas well
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Other (specify below)
☐ Insecticide storage

Direction from well? South West How many feet? 60

FROM	TO	LITHOLOG LOG	FROM	TO	PLUGGING INTERVALS
0	4	SURFACE SOIL - SANDY LOAM			
4	11	FINESAND			
11	20	COURSE SAND			
20	29	SMALL GRAVEL - COURSE SAND			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-3-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 12-18-92 under the business name of RALPH THEZGER WELL DIGGERS Ralph J. Metzger	
--	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.