

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 SE 1/4 NE 1/4	9	T 29 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 8340 S. LULU WICHITA KS 67233					
2 WATER WELL OWNER: MICHAEL MASON					
RR#, St. Address, Box #: 8340 S. LULU				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: WICHITA, KS 67233				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8 ft.			
		WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 6-11-93			
		Pump test data: Well water was 8 ft. after 2 hours pumping 25 gpm			
		Est. Yield 40 gpm: Well water was 8 ft. after 2 hours pumping 25 gpm			
		Bore Hole Diameter 11 in. to 29 ft. and 29 in. to 29 ft.			
WELL WATER TO BE USED AS:					
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☐					
5 TYPE OF BLANK CASING USED:					
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐ ☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded ☐ ☐ 7 Fiberglass Threaded ☐					
Blank casing diameter 5 in. to 21 ft. Dia 21 in. to 29 ft. Dia 29 in. to 29 ft. Dia 29 in. to 29 ft.					
Casing height above land surface 16 in. weight 2.37 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement ☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify) ☐ 9 ABS ☐ 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 8 Saw cut ☐ 11 None (open hole) ☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 7 Torch cut ☐ 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 21 ft. to 29 ft. From 21 ft. to 29 ft. From 21 ft. to 29 ft. From 21 ft. to 29 ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 29 ft. From 20 ft. to 29 ft. From 20 ft. to 29 ft. From 20 ft. to 29 ft.					
6 GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other 0-3' SURFACE SOIL					
Grout Intervals: From 3 ft. to 8 ft. From 8 ft. to 20 ft. From 20 ft. to 29 ft. From 29 ft. to 29 ft.					
What is the nearest source of possible contamination:					
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐ 13 Insecticide storage					
Direction from well? EAST How many feet? 54					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	SANDY LOAM TOP SOIL			
3	8	FINE SAND - STREAKS OF SILT			
8	29	COURSE SAND SMALL GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-11-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 6-14-93 under the business name of RALPH METZGER WELL DIGGER DRILLING Ralph S. Metzger					