

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: NW 1/4 NE 1/4 NE 1/4 Section Number: 9 Township Number: 29 S Range Number: 1 E

Distance and direction from nearest town or city street address of well if located within city? 1325 E 79th South Wichita, KS 67213

2 WATER WELL OWNER: Raymond Fields RR#, St. Address, Box #: 8027 S Lulu City, State, ZIP Code: Wichita, KS 67213

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: 28 ft. ELEVATION: 6-8-93

WELL'S STATIC WATER LEVEL: 9 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 9 ft. after 2 hours pumping 30 gpm

Est. Yield: 40 gpm; Well water was 9 ft. after 2 hours pumping 30 gpm

Bore Hole Diameter: 11 in. to 28 ft. and 28 in. to 28 ft.

WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below)

2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below), 2 PVC, 4 ABS, 7 Fiberglass

CASING JOINTS: Glued, Clamped, Welded, Threaded

Blank casing diameter: 5 in. to 20 ft. Dia. 2.37 in. to 2.50 ft. Dia.

Casing height above land surface: 22 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 2.50

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 11 Other (specify), 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole)

1 Continuous slot, 3 Mill slot, 6 Wire wrapped, 9 Drilled holes

2 Louvered shutter, 4 Key punched, 7 Torch cut, 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 28 ft. From 20 ft. to 28 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 28 ft. From 20 ft. to 28 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other 0-3' SURFACE SOIL

Grout Intervals: From 3 ft. to 9 ft. From 9 ft. to 20 ft. From 20 ft. to 28 ft.

What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage

Direction from well? North How many feet? 100

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 6-9-93 under the business name of RALPH THETZGER WELL DIGGING

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.