

1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 NE 1/4 Section Number 9 Township Number T 29 S Range Number R 1 EW
County: SEDGWICK
Distance and direction from nearest town or city street address of well if located within city?
8341 S VICTORIA WICHITA, KANSAS 67233
2 WATER WELL OWNER: TIM HENDRICKS
RR#, St. Address, Box #: 3937 N. SOMERSET
City, State, ZIP Code: WICHITA, KANSAS 67204
Board of Agriculture, Division of Water Resources
Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
N
NW NE
SW SE
S
W E
1 Mile
4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 8 ft. 2. 8 ft. 3. 8-25-93 ft.
WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr 8-25-93
Pump test data: Well water was 8 ft. after 2 hours pumping 30 gpm
Est. Yield 45 gpm: Well water was 8 ft. after 2 hours pumping 30 gpm
Bore Hole Diameter . in. to . ft., and . in. to . ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) Welded
2 PVC 4 ABS Threaded
Blank casing diameter 5 in. to 20 ft., Dia . in. to . ft., Dia . in. to . ft.
Casing height above land surface 18 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 20 ft. to 29 ft., From . ft. to . ft.
GRAVEL PACK INTERVALS: From 20 ft. to 29 ft., From . ft. to . ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL
Grout Intervals: From 3 ft. to 8 ft., From 8 ft. to 20 ft., From . ft. to . ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? WEST How many feet? 80
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 4 SURFACE SOIL
4 10 FINE SAND
10 29 COURSE SAND SMALL GRAVEL
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-25-93 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 9-3-93
under the business name of RALPH THETZGER WELL DIGGER DRILLER (Signature) Ralph J. Metzger
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.