

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE ¼ SW ¼ NE ¼	9	T 29 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1227 E 83rd South Wichita Kansas 67233					
2 WATER WELL OWNER: GREG SHAW RR#, St. Address, Box #: 1531 E 84th ST SOUTH City, State, ZIP Code: WICHITA KANSAS 67233					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 9 ft.			
		Depth(s) Groundwater Encountered 1. 9 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 9 ft. below land surface measured on mo/day/yr 8-26-87			
		Pump test data: Well water was 9 ft. after 2 hours pumping 40 gpm			
		Est. Yield 60 gpm; Well water was 9 ft. after 2 hours pumping 40 gpm			
		Bore Hole Diameter 10 in. to 30 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 20 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 16 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 9 ft. to 30 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL					
Grout Intervals: From 3 ft. to 9 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? SOUTH EAST How many feet? 50					
LITHOLOGIC LOG			LITHOLOGIC LOG		
FROM	TO		FROM	TO	
0	4	SURFACE SOIL			
4	9	CLAY			
9	15	FINE SAND			
15	30	COURSE SAND - SMALL GRAIN			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-26-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 8-26-87 under the business name of RALPH THEZORE WELLS DIGGERS INC. Ralph S. Thezore					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					