

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 9 Township Number: T 29 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city?
1/4 MILE SOUTH OF HAYSVILLE, KS 8220 S. BROADWAY WICHITA, KS

2 WATER WELL OWNER: M.A. HUNTER
RR#, St. Address, Box #: 8220 S. BROADWAY
City, State, ZIP Code: WICHITA KANSAS 67233

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 24 ft. ELEVATION: 10-5-82
Depth(s) Groundwater Encountered: 11 ft. 2. 11 ft. 3. 40 ft.
WELL'S STATIC WATER LEVEL: 11 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 11 ft. after 1.5 hours pumping 40 gpm
Est. Yield 60 gpm: Well water was 11 ft. after 1.5 hours pumping 40 gpm
Bore Hole Diameter: 10 in. to 13 in. and 8.5 in. to 24 in.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 6 in. to 14 in. Dia. 1.68 in. to 2.50 in. Dia. 1.68 in. to 2.50 in. Dia.
Casing height above land surface 14 in. weight 1.68 lbs./ft. Wall thickness or gauge No. 2.50
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 14 ft. to 24 ft. From 14 ft. to 24 ft.
GRAVEL PACK INTERVALS: From 14 ft. to 24 ft. From 14 ft. to 24 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 24 ft. From 10 ft. to 24 ft. From 10 ft. to 24 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage WATER WELL IN USE
Direction from well? NORTH How many feet? 8

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-6-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 10-9-82 under the business name of RALPH METZGER WELL DIGGER DRILLING (Signature) Ralph Metzger

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.