

1 LOCATION OF WATER WELL: County: Sedgewick Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 10 Township Number: T 29 S Range Number: R 10 E Distance and direction from nearest town or city street address of well if located within city? 1/2 West Derby KS.

2 WATER WELL OWNER: RR#, St. Address, Box #: Gary Williams 555 So Morgan Derby KS City, State, ZIP Code: Derby KS

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid of sections with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 271 ft. below land surface measured on mo/day/yr 5-17-83

WELL'S STATIC WATER LEVEL: 271 ft. below land surface measured on mo/day/yr 5-17-83

Pump test data: Well water was 22 ft. after 10 hours pumping 20 gpm

Est. Yield 50 gpm: Well water was 35 ft. after 20 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 35 ft. and 11 in. to 35 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter: 5 in. to 20 ft. Dia 1.59 in. to 20 ft. Dia

Casing height above land surface: 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No 50-26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft. From 13 ft. to 35 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 35 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 35 ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? North

How many feet? 125

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-1-83 under the business name of Wminger Drilling by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.