


Sent to Leonard
6/20/77

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

NW SE SE NW

1. Location of well:	County SEDGWICK	Fraction NE 1/4 SW 1/4 SE 1/4	Section number 11	Township number T 29 S	Range number R 1 E
2. Distance and direction from nearest town or city: 1/2 MILE WEST OF DERBY KANS Street address of well location if in city: LANE DERBY KANS		3. Owner of well: CAMELOT CONSTRUCTION INC. R.R. or street: 706 N MAIN WICHITA KANS City, state, zip code: 67202			
4. Locate with "X" in section below: 		Sketch map: BORED 8" HOLE TO 6.5 FT. INSTALLED 4" CASING - DROVE POINT TO COMPLETION - GROUTED CASING		6. Bore hole dia. 8 in. Completion date 4-30-77 Well depth 16.5 FROM 6' BASEMENT	
5. Type and color of material		From	To	7. ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary	
SAND MEDIUM TAN		0	3	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
SAND COARSE BROWN		3	6.5	9. Casing: Material RMP Height: Above or below Threaded ☒ Welded ☒ Surface 11" BASEMENT RMP ☒ PVC ☐ Weight 155 lbs./ft.	
H²O DROVE 1.25		6.5		Dia. 4 in. to 7.5 ft. depth Wall Thickness: inches or Dia. 4 in. to 7.5 ft. depth gage No. 1200	
SAND POINT + PIPE TO		16.5		10. Screen: Manufacturer's name CLAYTON MARK Type BRASS Dia. 1.25" Slot/gauze .060 Length 4 FT. Set between 12.5 ft. and 16.5 ft. ft. and 16.5 ft. Gravel pack? NO Size range of material	
				11. Static water level: 65 ft. below land surface Date 4-30-77	
				12. Pumping level below land surfaces: ft. after NA hrs. pumping NA g.p.m. ft. after 40 hrs. pumping 40 g.p.m. Estimated maximum yield 40 g.p.m.	
				13. Water sample submitted: mo./day/yr. Yes ☒ No ☐ Date	
				14. Well head completion: Pitless adapter 12 inches above grade	
				15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 0 ft. to 6.5 ft.	
				16. Nearest source of possible contamination: ft. 15 Direction SO. Type PLASTIC SEWER Well disinfected upon completion? ☒ Yes ☐ No	
				17. Pump: Not installed Manufacturer's name F.F.W. Model number 70P75 HP 1.75 Volts 230 Length of drop pipe 16.5 ft. capacity 18 g.p.m. Type: ☒ Submersible ☐ Turbine ☒ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
18. Elevation: 1300 Topography: ☐ Hill ☐ Slope ☐ Upland ☒ Valley		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP & WELL 1041 Business name BEARDEN PUMP & WELL License No. 1041 Address 342 MENTOR WICHITA KANS Signed W. Bearden Date 5-30-77 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5