

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

SE NE SE NW

29 1 E 1 1 S W E
T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	SEDGWICK	SALEM	SW 1/4 38 1/4	11	T29S	R1E
Distance and direction from nearest town or city: OF DERBY KANS 1 1/2 MILE WEST			3 Owner of well: CAMELOT CONSTRUCTION INC. Address: 706 N MAIN WICHITA KANS, 67202			
Street address of well location if in city: 8300 HANCOCK						
Locate with "X" in section below: N W E S 1 Mile			Sketch map: DRILLED 8" HOLE TO 7 FT. INSTALLED 4" CASING & GROUTED -		4 Well depth: 16.5 ft. Date of completion 9-26-75 Well diameter 8 in.	
					5 ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary	
					6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐	
					7 Casing: Material RMD Height: above/below BASEMENT FLOOR - Threaded ☐ Welded ☒ Surface 12 in. BASE- Diam. 30L Weight 655 lbs./ft. MENT 4 in. to 8 ft. depth Drive shoe? ☐ Yes ☒ No 3' in. to ft. depth DEE	
2 Type and color of material			From	To	8 Screen: Manufacturer MIDWEST Type BRASS Dia. 1.25 Slot gauge .060 Length 4 FT. Set between 12.5 ft. and 16.5 ft. Fittings: GALV. PIPE (IRON) & COUPLING Gravel pack ☐ Yes ☒ No Size range of material	
MEDIUM SAND - TAN COLOR			0	6.5		
WATER BEARING SAND - H ₂ O			6.5	7		
DROVE 1.25" SAND PIPE			7			
WITH SAND POINT TO -			16.5			
					9 Static water level: BASEMENT FLOOR 7 ft. below land surface Date 9-26-75	
					10 Pumping level below land surface: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 50 g.p.m.	
					11 Water sample submitted: ☐ Yes ☒ No Date	
					12 Well head completion: 12" BASEMENT FLOOR ☐ Pitless adapter ☒ Inches above grade	
					13 Well grouted? ☒ Yes ☐ No ☒ Neat cement ☐ Bentonite ☐ Depth: From 0 ft. to 7 ft. 29	
					14 Nearest source of possible contamination: ft. 10 Direction EAST Type WATER TITE Well disinfected upon completion? ☒ Yes ☐ No SEWER	
					15 Pump: Manufacturer's name FJW Model number 7007 HP .75 Volts 220 Length of drop pipe 16.5 ft. capacity 18 g.p.p. Type: ☐ Submersible ☐ Turbine ☒ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other 1 E 1 1	
16 Remarks: elevation 1300 FT.			17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Business name BEARDEN PUMP & WELL 1042 Address 3442 MENTOR - WICHITA KS Signed [Signature] Date 10/15/75 Authorized representative			

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5