


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

SE NE SE NW

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Fraction	Section number	Town number	Range number
	SEDGWICK	SALEM	SW 1/4, 9E 1/4	11	7295	R1E
Distance and direction from nearest town or city:		1/2 MILE WEST		3 Owner of well: CAMELOT CONSTRUCTION		
Street address of well location if in city:		8252 HANCOCK DRIVE		Address: 82706 N. MAIN, WICHITA, KS 67202		
Locate with "X" in section below:		Sketch map:		4 Well depth: 17 ft. Date of completion 4-7-76		
		BORED 8" HOLE TO 8.5 FT. INSTALLED 4" CASING. DROVE POINT TO COMPLETION GRouted CASING		Well diameter: 8 in.		
2		Type and color of material		From	To	5 ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary
		SANDY SUBSOIL RED BROWN		0	2	6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well
		SAND - TAN - FINE		2	6.5	7 Casing: ☒ Material ☐ Height: ☐ Above/below
		MED SAND - REDDISH		6.5	8.0	Thread: ☒ Surface ☐ in
		H ₂ O - WATER-BEARING SAND		8.5	9.0	Diam: ☒ Weight: ☐ lbs./ft.
		DROVE 1.25 GALV. PIPE		9		In. to ☐ ft. depth Drive shoe? ☐ Yes ☒ No
		W/ SAND POINT TO -			17	— in. to — ft. depth
						8 Screen:
						Manufacturer: CLAYTON MARK
						Type: BRASS Dia. 1.25
						Slot/gauge: 0.60 Length: 4 FT.
						Set between 13 ft. and 17 ft.
						Fittings: GALV PIPE + COUPLINGS
						Gravel pack ☐ Yes ☒ No Size range of material —
						9 Static water level:
						8.5 ft. below land surface Date 4-7-76
						10 Pumping level below land surfaces:
						— ft. after — hrs. pumping N/A g.p.m.
						— ft. after — hrs. pumping — g.p.m.
						Estimated maximum yield 50 g.p.m.
						11 Water sample submitted:
						☐ Yes ☒ No Date —
						12 Well head completion:
						☐ Pitless adapter ☒ 12" ABOVE BASEMENT
						13 Well grouted? ☒ Yes ☐ No
						☒ Neat cement ☐ Bentonite ☐ —
						Depth: From 0 ft. to 8.5 ft.
						14 Nearest source of possible contamination:
						ft. 11 Direction S.E. Type PLASTIC WATER SEWAGE
						Well disinfected upon completion? ☒ Yes ☐ No
						15 Pump:
						☐ Not installed
						Manufacturer's name F46
						Model number 7005 HP 25 Volts 220V
						Length of drop pipe 17 ft. capacity 18 g.m.p.
						Type:
						☐ Submersible ☐ Turbine
						☒ Jet ☐ Reciprocating
						☐ Centrifugal ☐ Other
16 Remarks: elevation				17 Water well contractor's certification:		
1300'				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Topography:				BEARDED PUMPWELL 1048		
☐ Hill				Business name License No.		
☐ Slope				Address: 312 MENTOR WICHITA, KS		
☐ Upland				Signed: [Signature] Date: 5/8/76		
☒ Valley				Authorized representative		

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5