

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

NW SE SE NW

1. Location of well:	County SEDGWICK	Fraction NW 1/4 SW 1/4 SE 1/4	Section number 11	Township number T29S	Range number R10E												
2. Distance and direction from nearest town or city: 1/2 MILE WEST OF DERBY KS.		3. Owner of well: RICHARD KROBUSEK															
Street address of well location if in city: 8332 PEACH LANE - DERBY KANS		R.R. or street: 8332 PEACH LANE															
		City, state, zip code: DERBY KANS-67037															
4. Locate with "X" in section below:		Sketch map: DRILLED 9" HOLE TO 10 FT. THEN 6" TO 13 FT. COMPLETED WELL WITH SAND BUCKET.		6. Bore hole dia. 9 in. Completion date 10-5-79 Well depth 22 ft. FROM GRADE													
		7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary															
		8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☒ Lawn ☐ Oil field water ☐ Other															
5. Type and color of material <table border="1"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>SAND MED. TAN</td> <td>0</td> <td>12</td> </tr> <tr> <td>SAND FINE TAN</td> <td>12</td> <td>16</td> </tr> <tr> <td>SAND COARSE TAN</td> <td>16</td> <td>22</td> </tr> </tbody> </table>			From	To	SAND MED. TAN	0	12	SAND FINE TAN	12	16	SAND COARSE TAN	16	22	9. Casing: Material RMP Height: Above or below Threaded ☒ Welded ☐ Surface 12 in. RMP ☒ PVC ☐ Weight 155 lbs./ft. Dia. 5 in. to 23 ft. depth Wall Thickness: inches or Dia. 5 in. to 23 ft. depth gage No. 0200			
			From	To													
SAND MED. TAN	0	12															
SAND FINE TAN	12	16															
SAND COARSE TAN	16	22															
10. Screen: Manufacturer's name SUN FLOWER Type RMP Dia. 5 INCH Slot/gauze .031 Length 6 FT. Set between 16 ft. and 22 ft. Gravel pack? NO Size range of material _____																	
		11. Static water level: _____ mo./day/yr. 13 ft. below land surface Date 10-5-79															
		12. Pumping level below land surfaces: _____ ft. after _____ hrs. pumping NA g.p.m. _____ ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield 50 g.p.m.															
		13. Water sample submitted: _____ mo./day/yr. ☒ Yes ☐ No Date _____															
		14. Well head completion: _____ Pitless adapter 12 inches above grade															
		15. Well grouted? YES With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From 0 ft. to 10 ft.															
		16. Nearest source of possible contamination: ft. 55 Direction S.W. Type SEPTIC Well disinfected upon completion? ☐ Yes ☒ No															
		17. Pump: ☒ Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other															
18. Elevation: 1300 FT.		19. Remarks:															
Topography: ☐ Hill ☐ Slope ☐ Upland ☒ Valley		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMPELL Business name _____ License No. _____ Address 3142 MENTOR WICHITA Signed O. W. Bearden Date 10-1-79 Authorized representative															

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5