

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

SE SW NW NE

1. Location of well:	County JEDGWICK	Fraction NE 1/4 SW 1/4 SE 1/4	Section number 11	Township number T 29	Range number S R 1E	E/W
2. Distance and direction from nearest town or city: 1/2 MILE WEST OF DERBY KS		3. Owner of well: CAMRLOT CONSTRUCTION R.R. or street: 706 N MAIN City, state, zip code: WILKITA, KS 67202				
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile		Sketch map: BORED 8" HOLE TO 6.5 FT, IN- STALLED 4" CASING DROVE SAND POINT TO COMPLETION ORUTED CASING		6. Bore hole dia. 8 in. Completion date 10-25 Well depth 19 ft. FROM 5' BASEMENT		
5. Type and color of material		From		To		7. ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary
		SAND, MEDIUM TAN		0 2.5		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other
SAND COARSE RED		2.5 6.5		9. Casing: Material RMP Height Above or below Threaded SOL Welded ☒ Surface 12 in. RMP 4 PVC 75 Weight 155 lbs./ft. Dia. 4 in. to 75 ft. depth Wall Thickness: inches or Dia. 4 in. to 75 ft. depth gage No. 200		
H ² O. DROVE 1.25 SAND		6.5		10. Screen: Manufacturer's name CLAYTON MARK Type BRASS Dia. 1.75 IN. Slot/gauze .060 Length 4 FT. Set between 15 ft. and 19 ft. ft. and ft. Gravel pack? NO Size range of material		
POINT & PIPE TO		19		11. Static water level: 6.5 ft. below land surface BASEMENT mo./day/yr. 77 Date 10-25		
				12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 40 g.p.m.		
				13. Water sample submitted: mo./day/yr. Yes ☒ No ☐ Date		
				14. Well head completion: 12 BASEMENT Pitless adapter inches above grade		
				15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 0 ft. to 6.5 ft.		
				16. Nearest source of possible contamination: ft. 10 Direction S.E. Type PLASTIC SEWER Well disinfected upon completion? ☒ Yes ☐ No		
				17. Pump: Not installed Manufacturer's name F&W Model number 70075 HP .075 Volts 230 Length of drop pipe 19 ft. capacity 18 g.p.m. Type: ☒ Submersible ☐ Turbine ☒ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
				(Use a second sheet if needed)		
18. Elevation: 1300 FT. Topography: ☐ Hill ☐ Slope ☐ Upland ☒ Valley	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP & WELL Business name 3422 MENTOR, WILKITA, KS License No. 104 Address 3422 MENTOR, WILKITA, KS Signed OTIS W. Bearden Date 11/16/15 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5