

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: SW 1/4 NW 1/4 SW 1/4 Section Number: 21 Township Number: T 29 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city? 2 1/4 MILE SOUTH OF HAYSVILLE KANSAS

2 WATER WELL OWNER: GORDON L CLARK RR#, St. Address, Box #: 2581 CROWNLEAF City, State, ZIP Code: WICHITA KANSAS 67226

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 14 ft. ELEVATION: 6-13-85

Depth(s) Groundwater Encountered: 9 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 9 ft. below land surface measured on mo/day/yr

Pump test data: Well water was No Pump Data hours pumping

Est. Yield: gpm: Well water was 14 ft. after hours pumping

Bore Hole Diameter: 4 in. to 14 in. to

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 2 Other (Specify below) WATER TABLE DETERMINED

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 2 in. to 9 ft. Dia. in. to ft. Dia. in. to ft. Dia.

Casing height above land surface: 12 in. weight: 5 lbs./ft. Wall thickness or gauge No. 167

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 9 ft. to 14 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 9 ft. to 14 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other SURFACE SOIL

Grout Intervals: From 0 ft. to 9 ft. From ft. to ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? W 125 How many feet? 250

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-13-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 6-15-85 under the business name of RALPH HOLTZMAN WELL DIGGER DRILLING RALPH J. HOLTZMAN

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.