


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County SEDERWICK	Fraction SW NE NE	Section number 21	Township number T 29 S	Range number R 1 E	E/W
2. Distance and direction from nearest town or city:		2 1/2 M WEST		3. Owner of well: WM Brockert			
Street address of well location if in city:		1 1/4 SO DERBY KANS		R. or street: 1229 EAST DEANA			
				City, state, zip code: WILHITA KANS, 67233			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 9 in. Completion date 6-28-78			
		BORED 9" HOLE TO 8 FT. H2O AT THIS DEPTH - SET CASING & USED SAND BUCKET TO COMPLETION		Well depth 31 ft. FROM GRADE			
5. Type and color of material		From		To		7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary	
SANDY LOAM BLACK		0		2		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
SANDY SUBSOIL BROWN		9		4		9. Casing: Material RMP Height: 16 in. Threading SEL Welded ☒ Surface 16 in. RMP ☒ PVC ☐ Weight 1.55 lbs./ft. Dia. 5 in. to 30 ft. depth Wall Thickness: inches or Dia. 0.200 in. to 0.200 ft. depth Gage No. 0.200	
SAND MEDIUM WHITE		4		6		10. Screen: Manufacturer's name SUN FLOWER	
SAND COARSE TAN-#20		6		8		Type RMP Dia. 5 INCH Slot/gauze 0.031 Length 6.5 FT. Set between 24.5 ft. and 31 ft. Gravel pack? NO Size range of material	
SAND MEDIUM TAN		8		14		11. Static water level: 8 ft. below land surface Date 6-28-78	
CLAY - GRAY		14		15		12. Pumping level below land surfaces: NA ft. after NA hrs. pumping g.p.m. NA ft. after NA hrs. pumping g.p.m. Estimated maximum yield 60 g.p.m.	
SAND COARSE GRAY		15		21		13. Water sample submitted: NO Yes ☒ No ☐ Date	
SAND CLAY - GRAY		21		22		14. Well head completion: 16 Pitless adapter 16 Inches above grade	
SAND COARSE GRAY		22		31		15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 0 ft. to 8 ft.	
						16. Nearest source of possible contamination: 35 ft. Direction WEST Type PLASTIC Well disinfected upon completion? ☒ Yes ☐ No	
						17. Pump: ☒ Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
18. Elevation: 1300 FT.		19. Remarks:		20. Water well contractor's certification:			
Topography: ☐ Hill ☐ Slope ☐ Upland ☒ Valley		OWNER WILL BUILD 4'X4'X4" REINFORCED CONCRETE SLAB		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMPWELL Business name License No. Address 3142 MENARD WILHITA KS Signed W. Bearden Date 7/28/78 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5