


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

NW NW NW SE

1. Location of well:	County SEDGWICK	Fraction NW 1/4 NE 1/4 SW 1/4	Section number 6	Township number T 29 S	Range number R 100 E/W
2. Distance and direction from nearest town or city: Street address of well location if in city: →			3. Owner of well: EDGAR E. ARMSTEAD R.R. or street: 509 WIRE City, state, zip code: HAYSVILLE KS, 67060		
4. Locate with "X" in section below: 			Sketch map: BORED 9" HOLE TO 10 FT. THEN 6 IN. TO 22.5 FT. - USED SAND BUCKET TO COMPLETE		
5. Type and color of material			From	To	6. Bore hole dia. 9 in. Completion date 4/14/78 Well depth 44 ft.
CLAY RED			0	3	7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary ☐
CLAY BLACK			3	4	8. Use: Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ ☒ Lawn ☐ Oil field water ☐ Other ☐
CLAY RED			4	12	9. Casing: Material RMP Height: 12 in. Above or below Threading SOL Welded ☒ Surface 12 in. RMP ☒ PVC ☐ Weight 455 lbs./ft.
CLAY YELLOW			12	18	Dia. 5 in. to 44 ft. depth, Wall Thickness: inches or Dia. 5 in. to 44 ft. depth, gage No. 200
SAND MED. YELLOW			18	22	10. Screen: Manufacturer's name SUNFLOWER Type RMP Dia. 5 INCH Slot/gauze 38 Length 6 FT. Set between 38 ft. and 44 ft. Gravel pack? NO Size range of material: _____
SAND MED TAN			22	27	11. Static water level: 22.5 ft. below land surface Date 4/14/78 mo./day/yr.
GRAVEL COARSE TAN			27	37	12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping NA g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 75 g.p.m.
GRAVEL COARSE BROWN			37	44	13. Water sample submitted: ____ mo./day/yr. Yes ☒ No ☐ Date _____
					14. Well head completion: ____ Pitless adapter 12 inches above grade
					15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 0 ft. to 10 ft.
					16. Nearest source of possible contamination: ft. 50 Direction 50 Type SEWER Well disinfected upon completion? Yes ☒ No ☐
					17. Pump: Not installed Manufacturer's name F+W Model number 50AS HP 50 Volts 115 Length of drop pipe 32 ft. capacity 12 g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP & WELL Business name 3142 MENTOR License No. W15H1A Address 000 W. Bearden Date 5/10/78 Signed 000 W. Bearden Authorized representative
18. Elevation: 1300 FT. Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley			19. Remarks:		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5