

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 NE 1/4 NE 1/4	6	T 29 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?					
115 W. GRAND AVENUE HAYSVILLE KS. 67060					
2 WATER WELL OWNER: T&COUNTRY MARKET		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : P.O. BOX 17087		Application Number:			
City, State, ZIP Code : WICHITA KS. 67217					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 1/4 in. to 20 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only X0 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
X2 PVC 4 ABS		Threaded			
Blank casing diameter 2 in. to 10 ft. Dia		in. to ft. Dia in. to ft.			
Casing height above land surface 0.5 in. weight sched 40		lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		X PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 10 ft.		From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 9 ft.		From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement X2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 8 ft. to 0.5 ft.		From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy X1 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? S/W		How many feet? 85			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.6	ASPHALT			
0.6	5'	topsoil turning to fine sand @ 4'			
5'	10'	fine grained sand			
10'	15'	fine to meduim g. sand			
15'	20'	meduim to course sand			
		a little gravel from 19'-20'			
		SATURATED AT 15'			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 11-23-94					
under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					