		10/0	TER WELL RE	CORD For	m WWC-5	Keva	32a-1212 I	ID No	NO HWS7					
1 LOCATION OF WATER WELL: Fraction				COND FOI	III VV VV C-O		ction Numb		ship Numb			ange Number		
그 County:	Wilson		NW1/4		" NE	1/4	16	т_	29	s	R	16	E/W	
Distance a	and direction	n from nearest to Quincy Alte	own or city stree	t address of v	vell if locat	ed within c	ity?							
	WELL OV	· · · · · · · · · · · · · · · · · · ·	Hrenak											
 RR#, St. <i>A</i>	Address, Bo , ZIP Code	x # : P.O. 1	Box 498 Ch	anute KS (	66720				of Agricu		Division of	f Water I	Resource	
		OCATION WITH						VATION:						
AN "X"	IN SECTION	N BOX:	Depth(s) Groun WELL'S STATION	dwater Encou	intered 1	l		ft. 2		ft. 3.			ft.	
<b>Ā</b> [	1	x						ft. after						
-	_NW	NE	Est. Yield	gpm:	Well water	was		ft. after		hours r	oumping . Oumping .		gpm apm	
•	] 	1	Bore Hole Dian	neter <b>8.2</b> .	5 in. to	15		ft., and			in. to		ft.	
- w  -	1		WELL WATER					8 Air condition			njection w			
	-sw	SE	1 Domestic 2 Irrigation	3 Feedlot 4 Industri			er supply vn & garden)	9 Dewatering 1 Monitoring			Other (Spe	-	-	
			Was a chemical	/hacteriological										
<u> </u>	' <u> </u> 		mitted	bactoriological	Sample Sub	milled to De		ater Well Disinf			no/uay/yr:	•	was sub X	
		CASING USED:	D.\	5 Wrought in		8 Conci			NG JOINT					
1 Stee		3 RMP (SI 4 ABS	H)	<ul><li>6 Asbestos-</li><li>7 Fiberglass</li></ul>			(specify be	elow)			ded		CT	
L	ing diamet	I D 2 04	§in. to											
		land surface	3.84	in., weight	0,8			bs./ft. Wall thick	kness or g	auge N	lo <b>S</b> C	H. 404.		
		OR PERFORAT	TION MATERIAL	<b>:</b>		7 PV	C	1	0 Asbesto	os-cem	ent	7		
1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile										r (specify)				
SCREEN	OR PERF	ORATION OPE			5 Gauze	d wrapped	- 	8 Saw cu		(	-	e (open	hole)	
	tinuous slo vered shut		ill slot ey punched		6 Wire w	• •		9 Drilled   10 Other (s						
		ATED INTERVAL		5			ft., Fr	om		ft. t				
	00445	PACK INTERVAL	From	3	. ft. to		ft., Fr	om		ft. t	0		ft.	
	GHAVEL	PACK INTERVAL	S: From From		.π.το .ft.to		π., Fr	om		ft. to	0 0		ft. ft.	
6 GROUT	MATERIA	AL: 1 Neat co	ement	2 Cement gr	out	3 Bento	nite	4 Other						
Grout Int	ervals: Fr	om	ft. to	.3ft., Fr	rom		. to	ft., Fro	om		ft. to		ft.	
		source of possib						estock pens			bandoned		/ell	
	tic tank ver lines	4 Later		7 Pit privy 8 Sewage lagoon			11 Fuel storage 12 Fertilizer storage			15 Oil well/Gas well 16 Other (specify below)				
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit					9 Feedyard			13 insecticide storage .			····Lust-Site·····			
Direction	from well?						How n	nany feet?				'		
FROM	ТО		ITHOLOGIC LO	OG		FROM	то		PLUGG	ING IN	ITERVAL	S		
0' 1'	15'	Concrete.	vn, silty, dry,	danca bio	. <b>L</b>									
<u> </u>	1.5	plasticity.		, uense, my	\$11 <b>4</b>									
		PARTICITY.												
	-													
· · · · · ·		<del>-  </del>												
	-									<del></del>				
						(4)			(0)			1		
		OR LANDOWNED (1974)						econstructed, coord is true to t						
		y/year) • / / • · r's Licence No								/13/9				
		ame of Corar						(signature)	MIN	11	Mh A	su		
		ewriter or ball point pen										exment of H	lealth and	
Environme	nt, Bureau of W	ater, Topeka, Kansas 6	6620-0001. Telephone	785-296-5524. Ser	nd one to WATE	R WELL OWN	ER and retain on	ne for your records. F	ee of \$5.00 for	each <u>con</u>	structed well.			