

1 LOCATION OF WATER WELL: County: Sedgwick Fraction NW 1/4 SW 1/4 SW 1/4 Section Number 36 Township Number T 29 S Range Number R 2 EW

Distance and direction from nearest town or city street address of well if located within city? Froms the SW cornr of Sec. 36, 1056' N., 564' E.

2 WATER WELL OWNER: Ralph Dohner RR#, St. Address, Box #: 11801 S. 145th Street E. City, State, ZIP Code: Mulvane, Ks. 67110 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with the SW section marked with an 'X']

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 1056' N., 564' E. Depth(s) Groundwater Encountered 1. 69 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 48' 4" ft. below land surface measured on mo/day/yr 10/2/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15+ gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 75 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 5 in. to 48' 4" ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 18 in. weight lbs./ft. Wall thickness or gauge No. 160 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 75 ft. to 48' 4" ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 75 ft. to 42 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 23 (3) ft. From 40 ft. to 42 (2) ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SW How many feet? 270

LITHOLOGIC LOG

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	5.0	Top soil and weathered clay			
5.0	17.0	Yellow, yellow gray clay			
17.0	37.0	Yellow gray clay			
37.0	62.0	Yellow brownish gray clay			
62.0	69.0	Dark gray to black clay			
69.0	74.0	Gray shale with thin gypsum stringers			
74.0	75.0	Gray clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/2/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 279 This Water Well Record was completed on (mo/day/yr) 10/2/95 under the business name of Fudge Drilling by (signature) Melvin R. Dudge

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.