

1 LOCATION OF WATER WELL: Fraction N 1/2 1/4 S 1/2 1/4 NE 1/4 Section Number 6 Township Number T 29 S Range Number R 2 EW

County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? 1229 Briarwood Ct. Derby, Kansas 67037

2 WATER WELL OWNER: William J. Stobbe RR#, St. Address, Box #: 1229 Briarwood Ct. City, State, ZIP Code: Derby, Kansas 67037 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the center square, labeled NW, NE, SW, SE. A scale bar indicates 1 mile. The grid is labeled N, S, E, W.]

4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION: Approx 1290' WELL'S STATIC WATER LEVEL: 8' ft. below land surface measured on mo/day/yr: Sept 15, 2002

Depth(s) Groundwater Encountered: 1. 8 ft. 2. 25 ft. 3. 40 (Main zone) ft. Pump test data: Well water was 33 ft. after 1 hours pumping @ 12 gpm Est. Yield 12 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 9 in. to 58 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter: 5 in. to 30 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface: 12 in. weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 58 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 58 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From Surface ft. to 2 ft. From 2 ft. to 30 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? 30' South of well How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Sept 15, 2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) October 6, 2002 under the business name of William J. Stobbe (Landowner) by signature William J. Stobbe

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.