

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: 1/4 3/4 1/2 1/4 1/4 Section Number: 6 Township Number: T 29 S Range Number: R 20 E

Distance and direction from nearest town or city street address of well if located within city? See below

2 WATER WELL OWNER: Judy Brahan RR#, St. Address, Box #: 1407 Evergreen Lane City, State, ZIP Code: Derby, KS 67037 63

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: Depth(s) Groundwater Encountered: 20 ft. 2. WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 3-15-02

Pump test data: Well water was 11 in. to 63 ft. after 11 hours pumping 33 gpm

Est. Yield 33 gpm Well water was 11 in. to 63 ft. after 11 hours pumping 33 gpm

Bore Hole Diameter: 11 in. to 63 ft. and 11 in. to 63 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter 11 in. to 23 ft. Dia 2.40 in. to 100 psi

Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 100 psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 23 ft. to 63 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 63 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 20 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft. From 20 ft. to 63 ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? West How many feet? 60

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-15-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 3-22-02 under the business name of Weninger Drilling Inc. by (signature) Dickie George

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.