

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW NW SW SE SE 1/4 NE 1/4 SE 1/4		SECTION NUMBER 6	TOWNSHIP NUMBER T 29 S	RANGE NUMBER R 2E E/W
Distance and direction from nearest town or city street address of well if located within city? 1307 Evergreen Lane Derby, Kansas						
2 WATER WELL OWNER: ROGERS, Juanita		Board of Agriculture, Division of Water Resource				
RR#,ST. ADDRESS,BOX #: 1307 Evergreen Lane		CITY, STATE: Derby, Kansas		ZIP CODE:	Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 82 ft. ELEVATION: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 10/7/03 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 82 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? <u>YES</u> NO				
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: <u>Glued</u> Threaded <u>2. PVC</u> 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped Blank casing diameter 5 in. to 32 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass <u>7. PVC</u> 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped <u>8. Saw cut</u> 10. Other (specify) SCREEN - PERFORATION INTERVAL From 32 ft. to 82 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 82 ft., From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIALS: 1. Neat cement <u>2. Cement Grout</u> 3. Bentonite Other <u>bentonite hole plug</u> Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) <u>3. Watertight sewer line</u> 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 12						
7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/7/2003 and this record is to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/10/2003 under the business name of Harp Well & Pump Service Inc. by (signature) <i>Jo dd S. Harp</i>						