

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>SE 1/4 SE 1/4 SW 1/4</u>	Section Number <u>20</u>	Township Number T <u>29S</u> S	Range Number R <u>2E</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>418 Fox Run Ct.</u>					
2 WATER WELL OWNER: <u>Chris Mitchell</u> RR#, St. Address, Box # : <u>418 Fox Run Ct.</u> City, State, ZIP Code : <u>Mulvane, KS</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <u>98</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>1 33</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>33</u> ft. below land surface measured on mo/day/yr <u>5/17/05</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Domestic (lawn & garden)</u> 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>98</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>16</u> in., weight <u>160</u> lbs./ft. Wall thickness or guage No. <u>26</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass <u>7 PVC</u> 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From <u>78</u> ft. to <u>98</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>98</u> ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>4</u> ft. to <u>24</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well <u>3 Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>West</u> How many feet? <u>30</u>					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	2	topsoil			
2	41	clay			
41	68	fine sand			
68	97	blue shale			
97	98	limestone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/17/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>6011</u> This Water Well Record was completed on (mo/day/yr) <u>6/8/05</u> under the business name of <u>Phage Drilling</u> by (signature) <u>P. Phage</u>					