

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Sedgewick Fraction: NE 1/4 NE 1/4 SE 1/4

Section Number

Township Number

Range Number

Distance and direction from nearest town or city street address of well if located within city? City

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude: _____

Longitude: _____

Elevation: _____

Datum: _____

Data Collection Method: _____

2 WATER WELL OWNER:


RR#, St. Address, Box #

City, State, ZIP Code

Bob Cook 5937
W 29 ST N
Wichita Kan 67205

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N



S

4 DEPTH OF COMPLETED WELL ft.

Depth(s) Groundwater Encountered (1) 65 ft. (2) ft. (3) ft.WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 70 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrSample was submitted Water well disinfected? Yes X No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)
2 PVC 4 ABS

5 Wrought Iron

6 Asbestos-Cement
7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued X Clamped

Welded

Threaded

Blank casing diameter in. to 5 ft. Diameter in. to ft. Diameter in. to ft.Casing height above land surface 18 in. Weight 160 lbs./ft. Wall thickness or gauge No. 1214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)SCREEN-PERFORATED INTERVALS: From 45 ft. to 106 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 OtherGrout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas wellDirection from well? S How many feet? 60

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 Soil
4 20 Shale
20 106 Shale & Lime7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 7/3/00 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 254 This Water Well Record was completed on (mo/day/year) 7/3/00under the business name of Winter Well Drill by (signature) Charles WinterINSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdhe.state.ks.us/geo/waterwells>.