

SE NE NE NW

# WATER WELL RECORD

Form WWC-5

KSA 82a-1212

ID No.

1 LOCATION OF WATER WELL: Fraction Township Number Range Number  
County: Sedgwick NW 1/4 29 S R 2 E  
Distance and direction from nearest town or city street address of well if located within city?  
1944 N. Country Walk Ln. Mulvane

2 WATER WELL OWNER: Dennis Thrash  
RR#, St. Address, Box #: 1944 N. Country Walk Ln.  
City, State, ZIP Code: Mulvane  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
W SE  
S  
4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION:  
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.  
WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield gpm: Well water was ft. after hours pumping gpm  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
2 PVC 4 ABS 7 Fiberglass Threaded  
Blank casing diameter 5 in. to 90 ft., Dia in. to ft., Dia in. to ft.  
Casing height above land surface 16 in., weight 120 lbs./ft. Wall thickness or gauge No. 26  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement  
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)  
9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify) ft.  
SCREEN-PERFORATED INTERVALS: From 80 ft. to 90 ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 25 ft. to 90 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Water-tight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? East How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  
0 2 topsoil  
2 68 clay  
68 80 fine sand  
80 90 blue shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-16-06 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's Licence No. 1611 This Water Well Record was completed on (mo/day/yr) 5-16-06  
under the business name of Chase Drilling by (signature) D. Chase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.