


1	LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SW 1/4 NE 1/4	SECTION NUMBER 18	TOWNSHIP NUMBER T 29 S	RANGE NUMBER R 2E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

1312 Summerlun	Derby, Kansas
----------------	---------------

2	WATER WELL OWNER:	Morris, Leonard	
	RR#,ST. ADDRESS,BOX #:	1312 Summerlun	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Derby, Kansas	Application Number:
		ZIP CODE:	

1 Mile 	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 86 ft.	ELEVATION:	
	Depth of groundwater Encountered: _____ ft.		ft.		
	WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 6/26/06		mo/day/yr:		
	Pump test data:		Well water was _____ ft. after _____ hours of pumping @ _____ gpm		
Est. Yield: _____ gpm		Well water was _____ ft. after _____ hours of pumping @ _____ gpm		Bore Hole Diameter 12 in. to 86 ft. and _____ in. to _____ ft.	
WELL WATER TO BE USED AS:					
1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well					
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted					
Was Water Well Disinfected? <u>YES</u> NO					

5		TYPE OF CASING USED:				9. Other (Specify below)		CASING JOINTS: <u>Glued</u>		Threaded	
1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass				Welded	
<u>2. PVC</u>		4. ABS		6. Asbestos-Cement		8. Concrete tile		SDR-26		Clamped	
Blank casing diameter		5 in.		to 66 ft.,		Dia.		in.		to ft.	
Casing height above land surface:		12 in.,		Weight:		2.35 lbs. / ft.		Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel		3. Stainless Steel		5. Fiberglass		<u>7. PVC</u>		9. ABS		11. Other (specify)	
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)	
2. Louvered shutter		4. Key punched		6. Wire wrapped		<u>8. Saw cut</u>		10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From		66 ft.		to		86 ft.,		From ft. to ft.	
		From		ft.		to		ft.,		From ft. to ft.	
GRAVEL PACK INTERVALS:		From		24 ft.		to		86 ft.,		From ft. to ft.	
		From		ft.		to		ft.,		From ft. to ft.	

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:	From	4	ft.	to	24	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage							
	Direction from well? East				How many feet? 25 ft. plus						

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **6-26-2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **6-28-2006**

under the business name of **Harp Well and Pump Service** by (signature) *J o d d S. H a r p*