

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 SW 1/4	SECTION NUMBER 29	TOWNSHIP NUMBER T 29 S	RANGE NUMBER R 2E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

1645 Prarie Run Circle **Mulvane, Kansas**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 86 ft. ELEVATION:													
	Depth of groundwater Encountered: _____ ft.													
	WELL'S STATIC WATER LEVEL 45 FT. BELOW LAND SURFACE MEASURED ON 6/18/12													
	Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm													
	Bore Hole Diameter 12 in. to 86 ft. and _____ in. to _____ ft.													
WELL WATER TO BE USED AS: <table border="0" style="width: 100%;"> <tr> <td>1. Domestic</td> <td>3. Feedlot</td> <td>5. Public water supply</td> <td>7. <u>Lawn and garden only</u></td> <td>9. Dewatering</td> <td>11. Injection well</td> </tr> <tr> <td>2. Irrigation</td> <td>4. Industrial</td> <td>6. Oil field water supply</td> <td>8. Air conditioning</td> <td>10. Monitoring well</td> <td>12. Other (Specify below)</td> </tr> </table>			1. Domestic	3. Feedlot	5. Public water supply	7. <u>Lawn and garden only</u>	9. Dewatering	11. Injection well	2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning	10. Monitoring well	12. Other (Specify below)
1. Domestic	3. Feedlot	5. Public water supply	7. <u>Lawn and garden only</u>	9. Dewatering	11. Injection well									
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning	10. Monitoring well	12. Other (Specify below)									
Was a chemical/bacteriological sample submitted to Department? YES NO submitted _____ Was Water Well Disinfected? YES NO														

5	TYPE OF CASING USED:				9. Other (Specify below)		CASING JOINTS:		Glued	Threaded		
	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	SDR-26				Welded	Clamped		
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile								
	Blank casing diameter		5	in.	to	60	ft.,	Dia.	in.	to	ft.	
	Casing height above land surface:		12	in.,	Weight:	2.35	lbs. / ft.	Wall thickness or gauge No.		.214		
	TYPE OF SCREEN OR PERFORATION MATERIAL:											
	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)						
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)						
	SCREEN OR PERFORATION OPENINGS ARE:											
	1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes		11. None (open hole)					
	2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)							
	SCREEN - PERFORATION INTERVAL		From	60	ft.	to	86	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
	GRAVEL PACK INTERVALS:		From	24	ft.	to	86	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug			
	Grout Intervals:	From	4	ft.	to	24	ft.,	From	ft.	to	ft.,	From	ft.	to
What is the nearest source of possible contamination:														
1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well				
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)				
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage								
Direction from well?										How many feet?		50 ft. plus		
Northwest														

[illegible]

Todd S. Harp