WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER NW Sedgwick NE 1/4 SW 1/4 32 Т 29 S 2E É/W Distance and direction from nearest town or city street address of well if located within city? 615 N. Charles Mulvane, Kansas SHAW, George WATER WELL OWNER: Board of Agriculture, Division of Water Resource 615 N. Charles RR#,ST. ADDRE\$\$,BOX #: Mulvane, Kansas CITY, STATE: Application Number: ZIP CODE 80 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NW ΝE ft. after Est Yield: gpm Well water was hours of pumping @ gpm Ξ 12 to 80 Bore Hole Diameter ft. WELL WATER TO BE USED AS: 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well - 9W SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oll field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) Was Water Well Disinfected? NO submitted 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1 Steel 3. RPM (SR) Welded Clamped SDR-26 4. ABS 6. Asbestos-Cement 8. Concrete tile 2. PVC 5 Blank casing diameter 35 Dia. Dia. in. in to ft 12 2.35 Casing height above land surface: in Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 8. RMP (SR) 12. None used (open hole) 2 Brass 6. Concrete Tile Asbestos-Cement 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 35 ft. 80 From to ft., From ft to ft. ft. From to ft., From ft ft. to 24 GRAVEL PACK INTERVALS: ft. to 80 From ft., From ft. ft to From to ft.. From ft **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft... From ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard Watertight sewer line 6. Seepage pit Northwest How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τo From Τo topsoil 0 clay 15 clay and fine sand mix gray shale 75 80 limestone

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. physical under my jurisdiction and was completed on (mo/day/year) 2/17/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/19/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp