Form WWC-5 KSA 82a-1212 WATER WELL RECORD SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION NE SE SW20 29 R 2E E/W Sedgwick Т S 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 414 Qualridge Ct. Mulvane, Kansas MC CLELLAN, Kyle WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 414 Qualridge Ct. Mulvane, Kansas Application Number: CITY, STATE ZIP CODE 80 ft. ELEVATION: 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm ⋛ 12 to 80 ft Bore Hole Diameter and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering s₩ SE 3. Feedlot 5. Public water supply 7. Lawn and garden only 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) NO submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 in. 60 ft.. Dia. ft., Dia in. to ft. to 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 Casing height above land surface: TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile SCREEN OR PERFORATION OPENINGS ARE: 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 10. Other (specify) 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 60 ft 80 SCREEN - PERFORATION INTERVAL From to ft., From ft. ft. to ft ft., From From to ft. to ft. 24 ft. to 80 GRAVEL PACK INTERVALS: ft., From ft to From ft. From ft. to From ft. Other GROUT MATERIALS: bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft.. From ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5 Cess Pool 2. Sewer lines 3. Watertight sewer line 6. 5 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG То From From Τo 0 3 topsoil 3 65 clay 65 75 medium sand 75 80 gray shale under my jurisdiction and plugged Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3.

8/27/2014 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

8/29/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp