

PLUG

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 10 Township Number T 29 S Range Number R 2 E
 County Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
From 79th and Greenwich Rd. Approx 1/2 E. S. Side

2 WATER WELL OWNER: DARRELL E WINTER
 RR#, St. Address, Box #: 11919 E 79th
 City, State, ZIP Code: DERBY KS 67037
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 825 ft.
 Depth(s) Groundwater Encountered 1. 825 ft. 2. 825 ft. 3. 825 ft.
 WELL'S STATIC WATER LEVEL 825 ft. below land surface measured on mo/day/yr July 21, 1988
 Pump test data: Well water was 110 gpm. Well water was 110 gpm. hours pumping 110 gpm.
 Est. Yield 110 gpm. Well water was 110 gpm. hours pumping 110 gpm.
 Bore Hole Diameter 10 in. to 10 in. and 10 in. to 10 in.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass 8 Saw cut Threaded.
 Blank casing diameter 10 in. to 10 in. Dia. 10 in. to 10 in. Dia. 10 in. to 10 in. Dia.
 Casing height above land surface 10 in. weight 200 lbs./ft. Wall thickness or gauge No. 10
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 0 ft. to 80 ft. From 0 ft. to 80 ft. From 0 ft. to 80 ft.
 GRAVEL PACK INTERVALS: From 0 ft. to 80 ft. From 0 ft. to 80 ft. From 0 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 80 ft. From 0 ft. to 80 ft. From 0 ft. to 80 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? Down Slope How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	earth	80	3	clay & shale grout
4	45	yellow clay water	3	0	dirt
45	80	grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 21, 1988 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) July 30, 1988
 under the business name of Reisner Well Drilling (signature) John Reisner

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.