Form WWC-5 KSA 82a-1212 WATER WELL RECORD SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION 29 SWNE 32 Т S 2EE/W Sedgwick R 1/4 Distance and direction from nearest town or city street address of well if located within city? 2214 Limuel Ct. Wichita, Kansas COLLIER, Kevin WATER WELL OWNER: Board of Agriculture, Division of Water Resource 935 Cedar Brook Circle RR#,ST. ADDRESS,BOX #: Mulvane, Kansas CITY, STATE: ZIP CODE Application Number: <u>70</u> **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 7/27/17 ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: ΝX Pump test data: Well water was ft. after hours of pumping @ gpm NW Est. Yield: Well water was ft. after hours of pumping @ gpm gpm ≌ 12 Bore Hole Diameter in. and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr (NO Was a chemical/bacteriological sample submitted to Department? Was Water Well Disinfected? (YES) submitted TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6 Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter to 45 ft., Dia. to Dia. ft. 12 2.35 Casing height above land surface: in., Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3 Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 11. None (open hole) 8. Saw cut 10. Other (specify) 2. Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 45 70 ft. ft., From From to to ft. to ft., From From ft. ft. 24 **GRAVEL PACK INTERVALS:** 70 From ft.. From to ft. From ft. to ft.. From ft ft to **GROUT MATERIALS:** Other 6 bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: 24 From ft., to ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 6. Seepage pit 9. Feed yard 3. Watertight sewer line North Direction from well? How many feet? 50 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Tο topsoil 30 clay 30 medium sand 50 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/27/17 and this record is true to the best of my knowledge and belief.

This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb