Corrected

		RECORD		WWC-5		ivision of Wat			*** ***		
		Correction		e in Well Use		sources App. 1		Township Numb	Well ID	ge Number	
1 LOCATION OF WATER WELL: County: Sedgwick			Fraction NE 1/4 SW 1/4 SW 1/4	4 SE 1/4	≣¼ 5 T 2			R 2	∠ E □ W		
		Last Name: SM	ITH	First: TROY	Street or Rural Address where well is located (if unknown, distance and					distance and	
Business: Address:	624 BELL	direction from nearest town or intersection): If at owner's address, check here:									
Address:											
City: DERBY State: KS ZIP: 67037											
3 LOCAT		4 DEPTH	OF COM	IPLETED WELL:						(decimal degrees)	
	ON BOX:	32 ft.									
l I	N			3) ft., or 4) TER LEVEL:				WGS 84 ☑ NAI Latitude/Longitude:		AD 27	
		☐ below l	and surface.	, measured on (mo-day	-yr)	l 🗀 🙃		nit make/model:			
NWNE				measured on (mo-day	-yr). 8/12/20	! .!	(V	VAAS enabled? 🔲	Yes \square N		
Pump test data: Well w B afterhours				pumping		☐ Land Survey ☐ Topographic Map ☐ Online Mapper:					
Well w				vater was	ft.						
after hour. Estimated Yield:20			pumping	. gpm	6 Eleva	6 Elevation: 1299ft. ☑ Ground Level ☐ TOC					
S Bore Hole Diameter:			gpm 12 _{in to} 80	Source: □ Land Survey □ GPS □				GPS □ To	pographic Map		
	nile			in. to	ft. Other KOLAR						
7 WELL WATER TO BE USED AS:											
1. Domestic											
=					how many wells?						
ı —	☐ Livestock 8. ☐ Monitoring: w										
	2. Irrigation 9. Environmental Remed										
3. ☐ Feedlo 4. ☐ Industi] Air Sparge] Recovery	-	Extraction						
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):											
Water well disinfected? ✓ Yes □ No											
8 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded											
Casing diameter 5 in to 80 ft., Diameter in to ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 12 5 in Weight 160 lbs./ft. Wall thickness or gauge No. 26											
Casing height above land surface in. Weight!99 lbs./ft. Wall thickness or gauge No49											
Steel Stainless Steel Fiberglass ✓ PVC Other (Specify)											
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
☐ Continuous Slot ☑ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)											
SCREEN-PERFORATED INTERVALS: From .60 ft. to .80 ft., From ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From24 ft. to80 ft., From ft. to ft., From ft. to ft.											
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other											
Grout Interv	als: From	ft. to		. ft., From	ft. to	ft., From		ft. to	tt.		
Septic		le contaminati	on: Lateral Line	s 🔲 Pit Privy	ſ	Livestock Pe	ens	☐ Insectic	ide Storage		
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well											
✓ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well											
☐ Other (Specify) Direction from well? NORTH Distance from well? 17 Distance from well? 17											
10 FROM	TO		ITHOLOG		FROM	TO	LITI	IO. LOG (cont.) or	PLUGGING	GINTERVALS	
0	2	TOPSOIL									
2	33	CLAY									
33	41	SANDY CLA	·Υ		 	 					
41 60	77	CLAY SANDY CLA	V			+					
77	80	LIMESTONE			 						
	-	,			Notes:	, _			<u> </u>		
II CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged											
1		اسمسمم ممتنا ليسا	atad an (m	so dou woort N/1///)14 an	a this record	18 11111	e io ine besi di iii	y Kiiowicu;	ge and benefit	
Kancac W/a	iter Well ('o	ntractor's Lici	ense No. 4	ZUL Inis w	ater well k	ecord was co	mpici	cu on (mo uuy y	July 11111111		
under the b	usiness nan	e of Chase.	Drilling	TELL OWNED and retain	one for your r	cords Fee of \$	5.00 fo	r each constructed we			
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
Visit us at http://www.kdheks.gov/waterwell/index.html											