KOLAR Document ID: 1636244

WATER V				WWC-5			on of Wate					
		Correction		e in Well Use			rces App. N			Well ID		
1 LOCATION OF WATER WELL:FractionCounty:1/41/41/4						Section	tion Number Township Number Range Number T S R $\Box E \Box W$					
county.						T S R B W or Rural Address where well is located (if unknown, distance and						
2 WELL O Business:	ist Name:		First:		rection from nearest town or intersection): If at owner's address, check here:							
Address:												
Address:												
City:		1	State:	ZIP:								
3 LOCATE		ft.	5 Latitu	ıde [.]			(decimal degrees)					
WITH "X" IN SECTION BOX: Depth(s) Groundwater Encountered: 1)												
	N 2) ft. 3) ft., or 4) \Box								WGS 84 INAI		NAD 27	
	TER LEVEL:		Source for Latitude/Longitude:									
		 below land surface, measured on (mo-day-yr) above land surface, measured on (mo-day-yr) 										
NW	- NE	Pump test data: Well water was ft.				······· (WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map					NO)	
w	E	after					☐ Online Mapper:					
		Well water was ft.										
SW	- SE			ours pumping gpm								
			timated Yield:gpm			6 Elevation:ft. Ground Level TOC						
S 1 mil	Bore Hole I	ore Hole Diameter: in. to fi			and Source: Land Survey GPS Topographic I							
7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease 												
□ Household 6. □ Dewatering: how many wells?												
☐ Lawn & Garden 7. ☐ Aquifer Recharge:								\Box Cased \Box Uncased \Box Geotechnical				
	Livestock 8. Monitoring: well ID											
2. Irrigation	1			al Remediation: well I								
3. EFeedlot Soil Vapor E							b) Open Loop 🗌 Surface Discharge 🔲 Inj. of Water					
4. Industrial Recovery Injection 13. Other (specify):												
Was a chemical/bacteriological sample submitted to KDHE? \Box Yes \Box No If yes, date sample was submitted:												
Water well disinfected? Yes No												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter												
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
$\Box \text{ Steel} \qquad \Box \text{ Stainless Steel} \qquad \Box \text{ PVC} \qquad \Box \text{ Other (Specify)} \dots$												
Brass Galvanized Steel None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)												
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From												
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. o ft. o ft. o ft. ft. to ft. to ft. ft. to ft. ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft												
Grout Intervals: From												
Nearest source				potential source of co								
🗌 Septic Ta	unk		Lateral Line	s 🗌 Pit Privy		🗌 Li	vestock Pe	ns	Insection			
Sewer Lin			Cess Pool	🗌 Sewage L			uel Storage		Abando			
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well												
Direction from well? ft.												
10 FROM	TO		ITHOLOG		FRO				HO. LOG (cont.) or		GINTERVALS	
	-	-					-			2.2011		
ļ	Notes:											
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged												
under my jurisdiction and was completed on (mo-day-year) and this record is true to the best of my knowledge and belief.												
Kansas Water	r Well Con	tractor's Lice	ense No	This W	ater Well	Recor	rd was con	nple	ted on (mo-day-ye	ear)	-	
under the bus	siness name	of	<u></u>				<u></u>				<u></u>	
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.												
-		<u>ks.gov/waterwel</u>		, and, Geology Stelloll, I	JUD D W JdC		., 5unc +20,	rope	nu, nunsas 00012-130		SA 82a-1212	