

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW ¼ SE ¼ NW ¼	1	T 29 S	R 2 E EW
Distance and direction from nearest town or city street address of well if located within city: 1/3 E. of 143rd St. E., S. side of 75th St. S., Wichita, Ks.					
2) WATER WELL OWNER: Dick Bonner RR#, St. Address, Box #: 516 W. Grand City, State, ZIP Code: Haysville, Ks.		Board of Agriculture, Division of Water Resources Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N +-----+ --NW-- --NE-- X --SW-- --SE-- S		4) DEPTH OF COMPLETED WELL..... 105 ft. ELEVATION: Depth(s) Groundwater Encountered 1..... 85 ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 4-3-82. Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter... 11.... in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No...X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below)		CASING JOINTS: Glued .. X .. Clamped .. Welded .. Threaded ..	
Blank casing diameter 5 in. to 35 ft., Dia in. to ft., Dia in. to ft.		Cer-Mac Styrene SDR-26			
Casing height above land surface..... 12 in., weight 1,59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile		7 PVC 8 RMP (SR) 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 35 ft. to 105 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 105 ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NONE APPARENT			
Direction from well? FROM TO LITHOLOGIC LOG		How many feet?			
0 3 Topsoil					
3 17 Clay					
17 37 Brown Clay					
37 86 Brown Shale					
86 105 Grey Shale					
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-3-82 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-7-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnesen					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					