


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 NW 1/4 SE 1/4 Section Number: 7 Township Number: T 29 S Range Number: R 20 EW
 Distance and direction from nearest town or city street address of well if located within city?
See Below.

2 WATER WELL OWNER: G.P. Schuler
 RR#, St. Address, Box #: #1 Madapalla
 City, State, ZIP Code: DERBY KS 67037
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 74 ft. ELEVATION: 42 ft.
 Depth(s) Groundwater Encountered: 42 ft. 2. 42 ft. 3. 42 ft.
 WELL'S STATIC WATER LEVEL: 42 ft. below land surface measured on mo/day/yr 11-6-90
 Pump test data: Well water was 42 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 30-35 gpm: Well water was 42 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter: 11 in. to 74 ft. and 74 in. to 74 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 54 ft. Dia 54 in. to 74 ft. Dia 74 in. to 74 ft.
 Casing height above land surface: 12 in. weight 260 lbs./ft. Wall thickness or gauge No 160 PSI
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 8 RMP (SR) ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 54 ft. to 74 ft. From 74 ft. to 74 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 74 ft. From 74 ft. to 74 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 74 ft. From 74 ft. to 74 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? W. How many feet 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top So.	56	61	Med. Sand
2	29	Clay.	61	74	shale
29	38	fine sand.			
38	39	clay			
39	42	shale			
42	56	fine sand.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-6-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-12-90 under the business name of Weninger Dull by (signature) [Signature]