

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 NE 1/4 Section Number 17 Township Number T 29 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 2 East 2 South of Derby

2 WATER WELL OWNER: Charles R June Haysville KS
 RR#, St. Address, Box #: 336 S. Twin Pines Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: 67060 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION: 80 ft.
 Depth(s) Groundwater Encountered: 1 ft. 80 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 8 1/2 in. to 105 ft. after 105 hours pumping 150 gpm
 Est. Yield 150 gpm Well water was 8 1/2 in. to 105 ft. after 105 hours pumping 150 gpm
 Bore Hole Diameter: 8 1/2 in. to 105 ft. and 105 in. to 105 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted
 Water Well Disinfected? ☒ Yes ☐ No

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) ☐ 6 Asbestos-Cement ☐ 9 Other (specify below)
 2 PVC ☐ 4 ABS ☐ 7 Fiberglass ☐ CASING JOINTS: Glued ☒ Clamped ☐
 Blank casing diameter: 5 in. to 55 ft. Dia 55 in. to 55 ft. Dia 55 in. to 55 ft. Dia 55 in. to 55 ft. Dia
 Casing height above land surface: 18 in., weight 200 lbs./ft. Wall thickness or gauge No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 55 ft. to 105 ft. From 55 ft. to 105 ft. From 55 ft. to 105 ft. From 55 ft. to 105 ft.
 GRAVEL PACK INTERVALS: From 40 ft. to 105 ft. From 40 ft. to 105 ft. From 40 ft. to 105 ft. From 40 ft. to 105 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☒ 14 Abandoned water well ☐
 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐
 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐
 13 Insecticide storage ☐
 Direction from well: N. W. How many feet? 650

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Soil			
4	10	Clay			
10	16	30 Clay & Rock			
16	40	15 Shale			
40	70	15 Shale & Lime			
70	105	30 Lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/27/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 215 231 This Water Well Record was completed on (mo/day/yr) 6/20/84 under the business name of Winterwell Drilling by (signature) Charles R June
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.