

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4		31		T 29 S		R 2 EW	
Distance and direction from nearest town or city street address of well if located within city?								Amoco #7174	
125' Northwest of the intersection of Mulvane Street & 2nd Street, Mulvane, KS								52895059	
2 WATER WELL OWNER:		Amoco Oil Company				MW-1			
RR#, St. Address, Box # :		8700 Indian Creek Parkway, Bldg. 3, Suite 180				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Overland Park, KS 66120				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25.0 ft. ELEVATION: Approx. Surface Elev: 1240							
		Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 15.4 ft. below land surface measured on mo/day/yr 11/25/89							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9 in. to 25.0 ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X							
Blank casing diameter 2 in. to 9.5 ft. Dia		Casing height above land surface -4 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 9.5 ft. to 24.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 8.0 ft. to 25.0 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 6.5 ft. From 6.5 ft. to 8.0 ft. From ft. to ft.							
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage							
Direction from well? South		How many feet? 5							
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	.5	Asphalt							
.5	2.5	Dark Brown Fill Lean Clay							
2.5	6.5	Red-Brown Lean Clay							
6.5	17.5	Red-Brown Clayey Sand							
17.5	22.0	Light Brown Fine to Medium Sand							
22.0	25.0	Light Brown Medium to Coarse Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/21/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1-10-90 under the business name of Terracon Consultants, Inc. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send one to WATER WELL OWNER and retain one for your records.									