


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction 8W 1/4 NW 1/4 SE 1/4	Section Number 32	Township Number T 29 S	Range Number R 2 E
Distance and direction from nearest town or city street address of well if located within city? 532 EMERY MULVANE KANSAS 67110					
2 WATER WELL OWNER: MICHELE TACKER RR#, St. Address, Box #: 532 EMERY City, State, ZIP Code: MULVANE, KANSAS 67110 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 20 ft. 2. 20 ft. 3. 20 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 6-13-87 Pump test data: Well water was 22 ft. after 2 hours pumping 20 gpm Est. Yield 30 gpm: Well water was 32 ft. after 2 hours pumping 20 gpm Bore Hole Diameter 10 in. to 32 ft. and 32 in. to 32 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☒			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ Blank casing diameter 5 in. to 22 ft. Dia. 22 in. to 22 ft. Dia. 22 in. to 22 ft. Dia. 22 in. to 22 ft. Dia. Casing height above land surface 12 in. weight 237 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 22 38 SCREEN-PERFORATED INTERVALS: From 22 ft. to 38 ft. From 22 ft. to 38 ft. From 22 ft. to 38 ft. From 22 ft. to 38 ft. GRAVEL PACK INTERVALS: From 20 ft. to 38 ft. From 20 ft. to 38 ft. From 20 ft. to 38 ft. From 20 ft. to 38 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL Grout Intervals: From 3 ft. to 20 ft. From 20 ft. to 20 ft. From 20 ft. to 20 ft. From 20 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? SOUTH How many feet? 75					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-13-87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 6-13-87 under the business name of RALPH THEZECER WELL DIGGER DRILLING INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					