

Water Well Record Form WW/C-5 KSA 82a-1212												
1	LOCATION OF WATER WELL:			FRACTION			Section Number		Township Number		Range Number	
	Sedgwick			NW NW SE SE SE 1/4 SW 1/4 SE 1/4			32		T 29 S		R 2E E/W	

Distance and direction from nearest town or city street address of well if located within city?

406 Trail Drive Mulvane, Kansas

2	WATER WELL OWNER:	WELLERS, Joe
	RR#, ST. ADDRESS, BOX #:	406 Trail Drive
	CITY, STATE, ZIP CODE:	Mulvane, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4	DEPTH OF COMPLETED WELL	82	ft.	ELEVATION:	
	Depth(s) groundwater Encountered	1	ft.	2	ft.
	WELL'S STATIC WATER LEVEL	32	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr	08/19/1993

Pump test data:		Well water was		ft.	after	hours pumping	gpm
Est. Yield	gpm:	Well water was		ft.	after	hours pumping	gpm
Bore Hole Diameter	12	in.	to 82	ft.	and	in.	to

WELL WATER TO BE USED AS:		5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No **X** ; If yes, mo/day/yr sample was
submitted Water Well Disinfected? Yes **X** No

5	TYPE OF CASING USED:
---	----------------------

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASKING JOINTS:	Glued	▲ Champed
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)		Welded	
		7 Fiberglass	SDR-26		Threaded	

Blank casing Diameter	5	in.	to	42	ft.	Dia	in.	to	ft.	Dia	in.	to	ft.
Casing height above land surface	12	in.				weight	2.35	lbs. / ft.		Wall thickness or gauge No.			.214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	8 <u>RMP</u> (SR)	11 other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

1 Continuous slot	3 Mill slot	5 Chain wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	6 Wire wrapped	10 Other (specify)
		7 Torch cut	

SCREEN-PERFORATION INTERVALS:	from 42	ft. to 82	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 82	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4	ft. to 24	ft., From	ft. to	ft., From
					ft. to

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandon water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)

Direction from well? **West** How many feet? **75**

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
------	----	----------------	------	----	--------------------

0	3	topsoil
3	37	clay
37	42	fine sand
42	82	grey shale

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/19/1993 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12/14/93 Under the business name of Harp Well & Pump Service, Inc. by (signature) [Signature]