

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 SW 1/4 SE 1/4		Section Number 33		Township Number T 29 S		Range Number R 2E	
Distance and direction from nearest town or city street address of well if located within city? 1/2 West of Greenwich Rd., Northside of 119th S. Mulvane, Ks.									
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Eldon Ford Box 505 Mulvane, Ks.							
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 12-5-89							
		Depth(s) Groundwater Encountered 1. 8 ft. 2. 12-5-89 ft. 3. 12-5-89 ft. WELL'S STATIC WATER LEVEL 8 ft. below land surface measured on mo/day/yr Pump test data: Well water was 11 ft. after 50 hours pumping 12-5-89 gpm Est. Yield 11 gpm: Well water was 50 ft. after 12-5-89 hours pumping 12-5-89 gpm Bore Hole Diameter 11 in. to 50 ft., and 11 in. to 50 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted 12-5-89 Water Well Disinfected? Yes X No X							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 5 in. to 18 ft. Dia 18 in. to 18 ft. Dia 18 in. to 18 ft. Dia 18 in. to 18 ft. Dia Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) X 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) X SCREEN-PERFORATED INTERVALS: From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. GRAVEL PACK INTERVALS: From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft. From 18 ft. to 50 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other X Grout Intervals: From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? NW How many feet? 55									
LITHOLOGIC LOG FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 3 topsoil 3 11 clay 11 17 fine sand 17 50 grey shale									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-5-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-30-90 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send to three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									