

1 LOCATION OF WATER WELL: Fraction 1/4 NE 1/4 NW 1/4 SE 1/4 SW 1/4 T 29 S R 2 E Distance and direction from nearest town or city street address of well if located within city? 3 Mile E of Mulvane Kan

2 WATER WELL OWNER: Perry Sollenburger Board of Agriculture, Division of Water Resources RR# St. Address, Box # 11001 145.5 E Mulvane Kan Application Number: 67110

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with the center section (12) marked with an 'X']

4 DEPTH OF COMPLETED WELL: 145 ft. ELEVATION: 85 ft. Depth(s) Groundwater Encountered: 1. 50 ft. 2. 85 ft. WELL'S STATIC WATER LEVEL: 50 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 3 gpm Well water was 3 ft. after 3 hours pumping 3 gpm

Est. Yield 3 gpm Well water was 3 ft. after 3 hours pumping 3 gpm

Bore Hole Diameter: 9 1/2 in. to 10 ft. and 10 in. to 10 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 5 in. to 30 ft. Dia. 160 in. to 1214 lbs./ft. Wall thickness or gauge No. 1214

Casing height above land surface 18 in. weight 160 lbs./ft.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) NA

SCREEN-PERFORATED INTERVALS: From 145 ft. to 125 ft. From 125 ft. to 145 ft. From 145 ft. to 125 ft. From 125 ft. to 145 ft.

GRAVEL PACK INTERVALS: From 145 ft. to 125 ft. From 125 ft. to 145 ft. From 145 ft. to 125 ft. From 125 ft. to 145 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other Grout Intervals: From 0 ft. to 23 ft. From 23 ft. to 145 ft. From 145 ft. to 125 ft. From 125 ft. to 145 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool X Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? S-E How many feet? 150

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/11/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/year) 9/11/94 under the business name of Winter Well Drilling by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.