

1 LOCATION OF WATER WELL: County: Butler		Fraction SW ¼ NW ¼ NW ¼	Section Number 5	Township Number T 29 S	Range Number R 3 EW																																																												
Distance and direction from nearest town or city street address of well if located within city? 101 E. Berry, Rose Hill, Kansas																																																																	
2 WATER WELL OWNER: RR#, St. Address, Box # : Midtown Services Attn: Dick Showalter City, State, ZIP Code : P.O. Box 23, Rose Hill, Ks 67133 Board of Agriculture, Division of Water Resources Application Number: ---																																																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: --- Depth(s) Groundwater Encountered 1. 31 ft. 2. --- ft. 3. --- ft. WELL'S STATIC WATER LEVEL 33.34 ft. below land surface measured on mo/day/yr 7/23/96 Pump test data: Well water was --- ft. after --- hours pumping --- gpm Est. Yield --- gpm: Well water was --- ft. after --- hours pumping --- gpm Bore Hole Diameter 8.625 in. to 40 ft., and --- in. to --- ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well mw-6 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes --- No X If yes, mo/day/yr sample was submitted --- Water Well Disinfected? Yes --- No X																																																															
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter 2 in. to 25 ft., Dia --- in. to --- ft., Dia --- in. to --- ft. Casing height above land surface 0 in., weight SCH 40 PVC lbs./ft. Wall thickness or gauge No. --- 3 RMP (SR) 4 ABS TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft. 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued --- Clamped --- Welded --- Threaded X 10 Asbestos-cement 11 Other (specify) --- 12 None used (open hole) 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) --- 11 None (open hole) GRAVEL PACK INTERVALS: From 24 ft. to 40 ft.																																																																	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other --- Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 24 ft., From --- ft. to --- ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Contaminated Si Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>GL</td> <td>0.50</td> <td>Sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.50</td> <td>25.00</td> <td>Silty Clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25.00</td> <td>25.25</td> <td>Limestone, hard</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25.25</td> <td>28.75</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>28.75</td> <td>29.00</td> <td>Limestone</td> <td></td> <td></td> <td></td> </tr> <tr> <td>29.00</td> <td>36.75</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>36.75</td> <td>37.00</td> <td>Limestone</td> <td></td> <td></td> <td></td> </tr> <tr> <td>37.00</td> <td>40.00</td> <td>Shale</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40.00</td> <td>TD</td> <td>End of borehole</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	GL	0.50	Sand				0.50	25.00	Silty Clay				25.00	25.25	Limestone, hard				25.25	28.75	Shale				28.75	29.00	Limestone				29.00	36.75	Shale				36.75	37.00	Limestone				37.00	40.00	Shale				40.00	TD	End of borehole			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																												
GL	0.50	Sand																																																															
0.50	25.00	Silty Clay																																																															
25.00	25.25	Limestone, hard																																																															
25.25	28.75	Shale																																																															
28.75	29.00	Limestone																																																															
29.00	36.75	Shale																																																															
36.75	37.00	Limestone																																																															
37.00	40.00	Shale																																																															
40.00	TD	End of borehole																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/29/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 7/23/96 under the business name of Associated Environmental, Inc. by (signature) <i>[Signature]</i>																																																																	