

1 LOCATION OF WATER WELL:	Fraction <u>SE 1/4 SW 1/4 NE 1/4</u>	Section Number <u>3</u>	Township Number <u>T 29 S</u>	Range Number <u>R 3 E</u>
---------------------------	--------------------------------------	-------------------------	-------------------------------	---------------------------

County: Butler Distance and direction from nearest town or city street address of well if located within city?

625 E Showalter Rose Hill

2 WATER WELL OWNER: <u>Kenneth L. Graham</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>625 E Showalter</u>	Application Number:
City, State, ZIP Code: <u>Rose Hill, KS</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>85</u> ft. ELEVATION: <u>85</u> ft.
--	---

Depth(s) Groundwater Encountered 1. 78 ft. 2. 78 ft. 3. 78 ft.

WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 40 ft. gpm: Well water was 40 ft. ft. after 40 ft. hours pumping

Bore Hole Diameter 10 in. to 10 in. ft., and 10 in. to 10 in.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	9 Dewatering
	☒ Lawn and garden only	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yr sample was submitted 10 mo/day/yr

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile
1 Steel	3 RMP (SR)	6 Asbestos-Cement
☒ PVC	4 ABS	7 Fiberglass
Blank casing diameter <u>5</u> in. to <u>5</u> in. ft., Dia <u>5</u> in. to <u>5</u> in. ft., Dia <u>5</u> in. to <u>5</u> in. ft.		
Casing height above land surface <u>12</u> in., weight <u>160</u> lbs./ft. Wall thickness or gauge No. <u>160</u>		
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut
1 Continuous slot	☒ Mill slot	6 Wire wrapped
2 Louvered shutter	4 Key punched	7 Torch cut
SCREEN-PERFORATED INTERVALS: From <u>65</u> ft. to <u>85</u> ft.		
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>85</u> ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout
Grout Intervals: From <u>0</u> ft. to <u>3</u> ft.		
What is the nearest source of possible contamination:	☒ Bentonite	4 Other
1 Septic tank	4 Lateral lines	7 Pit privy
2 Sewer lines	5 Cess pool	8 Sewage lagoon
☒ Watertight sewer lines	6 Seepage pit	9 Feedyard
Direction from well? <u>South</u>		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	dirt			
3	7	brown clay			
7	44	yellow clay			
44	67	gray shale			
67	85	shale lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and completed on (mo/day/year) <u>6/20/99</u>	and this record is true to the best of my knowledge and belief. Kar
Water Well Contractor's License No. <u>493</u>	This Water Well Record was completed on (mo/day/yr) <u>6/20/99</u>
under the business name of <u>Reiserer Well Drilling</u>	by (signature) <u>John Reiserer</u>