

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Batter</u>	<u>SW 1/4 SW 1/4 SE 1/4</u>	<u>12</u>	T <u>29</u> S	R <u>3</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

2-W of Douglas 1 North

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RP#, St. Address, Box #	Application Number:
City, State, ZIP Code	

Ken Cokley Douglas Kan 6403910686 S.W. 210th St

3 LOCATE WELL'S LOCATION WITH	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
AN "X" IN SECTION BOX:	Depth(s) Groundwater Encountered	ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL	ft. below land surface measured on mo/day/yr
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield	gpm; Well water was
	Bore Hole Diameter	in. to ft., and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes. No. <u>X</u> ; If yes, mo/day/yr sample was submitted	
	Water Well Disinfected? Yes <u>X</u> No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. <u>X</u> Clamped.
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter	5 in. to ft., Dia	in. to ft., Dia	in. to ft.
Casing height above land surface	18 in., weight	160 lbs./ft. Wall thickness or gauge No.	214
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From	40 ft. to 105 ft.	ft. to ft.	ft. to ft.
GRAVEL PACK INTERVALS: From	ft. to ft.	ft. to ft.	ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From	3 ft. to 23 ft.	ft. to ft.	ft. to ft.	ft. to ft.
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?	<u>East</u>	How many feet?	<u>200</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Soil			
4	15	Clay			
15	20	Rock			
20	30	Gravel			
30	105	Shale + Lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)	12/18/02	and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No.	257	This Water Well Record was completed on (mo/day/yr)	12/28/02	under the business name of	Winter Well Drilling	by (signature)	Charles Winter
--	----------	--	-----	---	----------	----------------------------	----------------------	----------------	----------------