

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>	<u>C</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	<u>5</u>	T <u>29</u> S	R <u>3E</u> E/W

Distance and direction from nearest town or city street address of well if located within city?

549 Plumwood Dr., Rose Hill

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
<u>Kenny Lawrie</u>	<u>549 Plumwood Dr.</u>	<u>Rose Hill, KS 67133</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ft. ELEVATION:
	Depth(s) Groundwater Encountered <u>1</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>32</u> ft. below land surface measured on mo/day/yr <u>4-3-03</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <u>7</u> Domestic (lawn & garden) 10 Monitoring well	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	Blank casing diameter	in. to	ft., Dia	in. to	ft., Dia	in. to	ft., Dia	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel <u>2</u> PVC 3 RMP (SR) 4 ABS	<u>5</u>		<u>52</u>					Welded Threaded
Casing height above land surface	<u>12</u>	in., weight		lbs./ft. Wall thickness or gauge No.	<u>SDR26</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile								7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 2 Louvered shutter <u>3</u> Mill slot 4 Key punched								5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS:	From	<u>52</u>	ft. to	<u>92</u>	ft. to			
GRAVEL PACK INTERVALS:	From	<u>20</u>	ft. to	<u>92</u>	ft. to			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3</u> Bentonite	4 Other
Grout Intervals:	From	<u>4</u>	ft. to	<u>20</u>
What is the nearest source of possible contamination:				
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>20</u>	<u>dry</u>			
<u>20</u>	<u>32</u>	<u>shale</u>			
<u>32</u>	<u>33</u>	<u>lime</u>			
<u>33</u>	<u>57</u>	<u>lime & shale</u>			
<u>57</u>	<u>75</u>	<u>shale</u>			
<u>75</u>	<u>80</u>	<u>brown shale</u>			
<u>80</u>	<u>90</u>	<u>clayey lime</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was	(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)	<u>4-3-03</u>	and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No	<u>171</u>	This Water Well Record was completed on (mo/day/yr)	<u>4-22-03</u>	by (signature)	<u>[Signature]</u>
under the business name of				<u>G+S Drilling Inc.</u>				