

1 LOCATION OF WATER WELL: County: Butler Fraction: SW 1/4 SE 1/4 NW 1/4 Section Number: 2 Township Number: T 29 S Range Number: R 3 E

Distance and direction from nearest town or city street address of well if located within city? 4 East of Rose Hill

2 WATER WELL OWNER: Jerry Cook Rose Hill Kan 67133
RR#, St. Address, Box #: 7213 S Towakone Rd
City, State, ZIP Code: Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 105 ft. ELEVATION: 85 ft.
Depth(s) Groundwater Encountered 1. 85 ft. 2. 40 ft. 3. 40 ft.
WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 15 gpm; Well water was 8 1/2 ft. after 15 hours pumping 15 gpm
Est. Yield 15 gpm; Well water was 8 1/2 ft. after 15 hours pumping 15 gpm
Bore Hole Diameter: 8 1/2 in. to 8 1/2 in. and 8 1/2 in. to 8 1/2 in.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Threaded X
Blank casing diameter 5 in. to 5 in. ft. Dia 18 in. to 18 in. ft. Dia 160 lbs./ft. Wall thickness or gauge No. 214
Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No. 214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 12 None used (open hole)
SCREEN-PERFORATED INTERVALS: From 70 ft. to 105 ft. From 70 ft. to 105 ft. From 70 ft. to 105 ft. From 70 ft. to 105 ft.
GRAVEL PACK INTERVALS: From 70 ft. to 105 ft. From 70 ft. to 105 ft. From 70 ft. to 105 ft. From 70 ft. to 105 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 200
Grout Intervals: From 0 ft. to 20 ft. From 0 ft. to 20 ft. From 0 ft. to 20 ft. From 0 ft. to 20 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? S-West How many feet? 200

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/11/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 254 This Water Well Record was completed on (mo/day/yr) 12/27/90 under the business name of Winter Well Drill by (signature) Charles Winter

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.