

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number					
County: Butler		SE ¼ NE ¼ SE ¼		3		T 29 S		R 3 EW					
Distance and direction from nearest town or city? from Mid-Continent S&L in Rose Hill, E. 3 miles, 7/10 So., west side in field													
2 WATER WELL OWNER: Wayne Kelly													
RR#, St. Address, Box #: 1745 S Chautauqua						Board of Agriculture, Division of Water Resources							
City, State, ZIP Code: Wichita, Ks.						Application Number:							
3 DEPTH OF COMPLETED WELL: 68 ft. Bore Hole Diameter: 10 in. to 68 ft. and in. to ft.													
Well Water to be used as:													
☒ Domestic		3 Feedlot		5 Public water supply		8 Air conditioning		11 Injection well					
2 Irrigation		4 Industrial		6 Oil field water supply		9 Dewatering		12 Other (Specify below)					
		7 Lawn and garden only		10 Observation well		heat pump discharge							
Well's static water level: 27' 6" ft. below land surface measured on May month 9 day 1983 year													
Pump Test Data: Well water was ft. after hours pumping. gpm													
Est. Yield 12+ gpm: Well water was ft. after hours pumping. gpm													
4 TYPE OF BLANK CASING USED:													
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		Casing Joints: Glued ☒ Clamped					
☒ PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded					
				7 Fiberglass				Threaded					
Blank casing dia 5 in. to 68 ft. Dia in. to ft. Dia in. to ft.													
Casing height above land surface: 18 in., weight lbs./ft. Wall thickness or gauge No. 160													
TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ PVC													
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement					
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		11 Other (specify)					
								12 None used (open hole)					
Screen or Perforation Openings Are:													
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		☒ Saw cut		11 None (open hole)					
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes							
				7 Torch cut		10 Other (specify)							
Screen-Perforation Dia: 5 in. to 68 ft. Dia in. to ft. Dia in. to ft.													
Screen-Perforated Intervals: From 25 ft. to 68 ft., From ft. to ft., From ft. to ft.													
Gravel Pack Intervals: From 20 ft. to 68 ft., From ft. to ft., From ft. to ft.													
5 GROUT MATERIAL: ☒ Neat cement													
2 Cement grout		3 Bentonite		4 Other									
Grouted Intervals: From 3 1/2 ft. to 15 ft., From ft. to ft., From ft. to ft.													
What is the nearest source of possible contamination:													
☒ Septic tank		4 Cess pool		7 Sewage lagoon		11 Fertilizer storage		14 Abandoned water well					
2 Sewer lines		5 Seepage pit		8 Feed yard		12 Insecticide storage		15 Oil well/Gas well					
3 Lateral lines		6 Pit privy		9 Livestock pens		13 Watertight sewer lines		16 Other (specify below)					
Direction from well: to be installed by Butler Co. permit													
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, date sample was submitted month day year Pump Installed? Yes No ☒													
If Yes: Pump Manufacturer's name Model No. HP Volts													
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.													
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other													
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on May month 9 day 1983 year													
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 279													
This Water Well Record was completed on May month 9 day 1983 year under the business name of Fudge Drilling by (signature) Melvin R. Fudge													
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:													
		FROM		TO		LITHOLOGIC LOG		FROM		TO		LITHOLOGIC LOG	
		0		2		top soil		38		51		yellow gray shale	
		2		12		yellow gray shale with limestone strgs		51		62 1/2		yellow gray limestone	
		12		20		lavendar shale with interbedded green and gray shale		62 1/2		65		yellow gray shaley limestone, darker than the limestone above	
		20		20 1/2		yellow gray limestone		65		68		gray shale	
		20 1/2		27		lavendar shale becoming more gray with depth							
		27		38		gray shale							
ELEVATION:													
Depth(s) Groundwater Encountered 1. 20 ft. 2. 51 ft. 3. ft. 4. ft. (Use a second sheet if needed)													

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.