

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BUTLER		NE 1/4 NE 1/4 SE 1/4	27	T 29 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 3 W 1 1/2 S west side Douglass, KS					
2 WATER WELL OWNER: Dane K. Nixon					
RR#, St. Address, Box #: Rt 3 Box 4					
City, State, ZIP Code: Douglass, KS 67039					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 95' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 6/8/90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 30 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)			
		☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
☒ 2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 5 in. to ft. Dia		Casing height above land surface 12 in. weight		lbs./ft. Wall thickness or gauge No. 160	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
				7 PVC	
				8 RMP (SR)	
				9 ABS	
				10 Asbestos-cement	
				11 Other (specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		☒ 3 Mill slot		5 Gauzed wrapped	
2 Louvered shutter		4 Key punched		6 Wire wrapped	
				7 Torch cut	
				8 Saw cut	
				11 None (open hole)	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS:					
From 75 ft. to 95 ft.		From ft. to ft.			
From ft. to ft.		From ft. to ft.			
GRAVEL PACK INTERVALS:					
From 20 ft. to 95 ft.		From ft. to ft.			
From ft. to ft.		From ft. to ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		☒ 3 Bentonite	
4 Other					
Grout Intervals: From 3 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		☒ 8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? Down Slope					
How many feet? 50+					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	earth			
4	6	green shale			
6	10	gray shale (light)			
10	25	yellow clay			
25	38	gray shale			
38	45	red bed			
45	58	gray shale			
58	75	shale			
75	95	lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/8/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) 6/10/90 under the business name of Reisner Well Drilling by (signature) Jerry Reisner					