

1 LOCATION OF WATER WELL: County: <u>Butler</u>	Fraction: <u>NE 1/4 NW 1/4 SE 1/4</u>	Section Number: <u>2</u>	Township Number: <u>T 27 S</u>	Range Number: <u>R 3 E</u>
--	---------------------------------------	--------------------------	--------------------------------	----------------------------

Distance and direction from nearest town or city street address of well if located within city?

3-W 8-5 of Augusta

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code	<u>Sharp Cons. 410 State St. 67010</u> <u>Augusta Kan</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: <u>145</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 130 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 45 gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 2 1/2 in. to ft., and in. to ft.

WELL WATER TO BE USED AS:

☒ Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
------------------------------	----------------	-----------------	--

1 Steel

☒ 2 PVC

3 RMP (SR)

4 ABS

7 Fiberglass

Blank casing diameter 5 in. to 50 ft. Dia

Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No. 214

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement
---	--------------------

1 Steel

2 Brass

3 Stainless steel

4 Galvanized steel

5 Fiberglass

6 Concrete tile

8 RMP (SR)

9 ABS

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

2 Louvered shutter

3 Mill slot

4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS:	From <u>50</u> ft. to <u>145</u> ft.
------------------------------	--------------------------------------

GRAVEL PACK INTERVALS:	From ft. to ft.
------------------------	-----------------

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ 3 Bentonite	4 Other
-------------------	---------------	----------------	--	---------

Grout Intervals: From 0 ft. to 23 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	☒ 8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? SW How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<u>Soil</u>			
<u>4</u>	<u>10</u>	<u>Clay</u>			
<u>10</u>	<u>15</u>	<u>Rock</u>			
<u>15</u>	<u>145</u>	<u>Shale & Lime</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5/10/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>251</u> This Water Well Record was completed on (mo/day/yr) <u>5/15/95</u> under the business name of <u>Winter Well Drill</u> by (signature) <u>Charles Winter</u>
--